



The **IVSEC NC528XA** IP security camera offers a 5 Megapixel resolution sensor combined with a **5-50 mm vari-focal motorised lens** (50.9 to 7.6° field of view).

The built-in infrared illumination enables night vision at up to an **impressive 80 metres**.

When used together with the IVSEC X series recorders, this camera will be automatically detected with **Plug & Play**.

Reduce installation labour and parts required by using one cable for both data and electricity with PoE (Power over Ethernet).

The IVSEC NC528XA features an IP66 water resistant and anti-vandal bullet housing which means this video surveillance camera can be used both indoors and outdoors.

The NC528XA security camera features **H.265** video compression technology and is fully compatible with the **ONVIF 2.6 standard**.

It also offers on board **video analytics**: Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Pedestrian Detection, Face Detection, Cross Counting.

Main features: Bullet IP Camera, 5MP, motorised 5-50 mm lens, video analytics, PoE, IP66, 80m IR, ICR, 3 year warranty.

IVSEC NC528XA

IP Cameras

NC528XA Specifications	
Camera Type	Bullet
Outdoor Use	Outdoor Use
Vandal Resistant	Yes
Image Sensor	1/2.7" 5MP Progressive CMOS
Maximum Video Resolution	2592x1944
Maximum Video Resolution (Megapixels)	5
Frame Rate Resolution	15
Lens	5-50 mm (H. FOV 50.9 to 7.6°)
Lens Type	Motorised
Day/Night Mode	Auto IRC
Maximum Night IR Distance (M)	80
Dynamic Range	DWDR
Image Enhancement	Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue
Protocols	TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPnP, SMTP, SNMP, P2P (QR code)
ONVIF	YES 2.6
IVS	Yes
Intelligent Video	Motion Detection, Video Loss, Tampering Detection, Storage Exception, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Pedestrian Detection, Face Detection, Cross Counting
Software	Device Tool Manager, Video Monitoring Software, Mobile App.
Power Supply	Power over Ethernet (PoE) IEEE 802.3af, DC12V,
Connectors	RJ-45, DC Power Input, Analog Video Output, Audio In, Audio Out, Alarm in or out *4, reset button
UPNP	Yes
In The Box	Free Software available from FTP, Printed quick user guide, installation template, mounting screws and plugs
Model	NC528XA
Weight	1468
In Depth	Please refer to the Downloads Tab
Operating Environment	-10°C to 55°C (14°F-131°F) Humidity: 20%-80% RH
Warranty	36 months parts & labour warranty
Dimensions	108x301mm